

Acri-Soy

Penetrating Clear Sealer

Non Toxic Concrete & Wood Sealer

INTENDED USES:

- Decorative Concrete
- Warehouse Floors
- Garage Floors
- Masonry Block
- Brick Pavers
- Saltillo Tile
- Wood Decks
- Wood Siding
- Fiber Cement
- Plaster Walls

GREEN BUILDING ATTRIBUTES:

- Low Emitting Material
- Renewable Resource
- Recycled Content
- Innovation in Design
- Regional Materials
- Material Reuse

PROFESSIONAL ATTRIBUTES:

- UV Resistant
- Virtually Odorless
- Non Combustible
- 30-60 Minute Dry Time
- Highest Coverage Rates
- Breathable Chemistry
- Will Not Flake or Peel
- No Toxic Exposures
- Airless, Mop, or Pad Apply
- Fast Water Cleanup

SHEEN:

Natural Matte Finish



Made in the USA

Acri-Soy Penetrating Clear Sealer	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	A



- ✓ 100% natural plant oil, water and polymer emulsion that replicates petrochemical solvents without toxins or safety hazards.
- ✓ Penetrating chemistry to integrally bond and seal cementitious or wood surfaces that will never flake or peel.
- ✓ No VOC's, no toxic offgassing, and is virtually odorless.
- ✓ Fast dry times usually within 30 minutes to 1 hour to reduce labor time and offer a quick return to service.
- ✓ Excellent UV, efflorescence, and water resistance.
- ✓ Breathable chemistry that allows moisture to escape preventing delamination and premature substrate damage.

Description

Acri-Soy Penetrating Concrete Sealer & Wood Sealer provides a durable, long lasting integral bond and seal that will never flake or peel. The 100% natural oil derivatives and solvent free acrylic emulsion chemistry penetrates to fill the pores or fibers of the substrate to effectively seal out moisture, yet allows moisture vapors to escape which helps prevent premature degradation.

This advanced chemistry uses less material yielding a higher spread rate since you are not building a film. It will enhance your stained or natural substrate finish and won't make it look like a plastic or fake surface. Acri-Soy dries fast, typically within 30 to 60 minutes for a quick return to service and saves hours of labor time.

Once the sealer is cured, our unique proprietary resins have blocking properties that helps resist efflorescence formation on concrete and masonry surfaces. The natural oil resins also act as a natural preservative that restores some of the lost function of sap to preserve wood substrates.

Installation is fast, easy, and virtually odorless. When it is time for a maintenance recoat, there is no need to strip the sealer. Simply clean and reapply. Achieve durability and sustainability at the lowest cost per square feet while saving valuable labor time.

Technical Data

Typical Coverage: 400 - 800 Sq.Ft./Gallon
 Typical Dry Time: 30 Min. to 1 Hour
 Installation Temperature: 45°F - 100°F
 Regulatory V.O.C.: 0 g/L
 Bio-Based Content: <20%
 Recycled Content: <20%
 Flash Point: Non Flammable
 Clean Up: Soap & Water

Application Equipment Choices

Airless Sprayer: Tip Size .010 - .012.
 HVLP Sprayer: Standard Mist Spray
 90 PSI Pump Sprayer-Best, Use w/Pad or Buff
 Garden Sprayer- Good, Use w/Pad or Buff
 Stain Pad: Polyester Foam or Wool
 Nylon Foam Block Applicator
 Microfiber Mop Applicator
 Floor or Orbital Buffer

Non Toxic Ingredients:

Water, 100% Bio-Based Emulsion Mixture, Proprietary Solvent Free Emulsion Resin, Natural Preservative, Solvent Free Surfactants, Solvent Free Thickeners.

No Red List Chemicals

Part #'s

A1-3000 Series Acri-Soy Penetrating Sealer
 Available in 32 Oz, 1, 5, 55, 275 gallons