

EcoFast 500 HD Cleaner/Degreaser Installation Guide



STEP 01

PRE-TEST

For large cleaning task projects or when cleaning colorfast materials such as upholstery, carpets, etc., always test for compatibility and efficacy.

Testing a small area will help you identify the most effective dilution ratio. We supply you with a standard guide for a quick starting point.

Depending on the type of cleaning task and tools, keep in mind that heat will accelerate cleaning efficiency. This is a valuable attribute with heated pressure washer capability or if using heated dip tanks for degreasing oily or greasing parts.

STEP 02

TOOLS/MATERIALS

Mechanical Tool Options:
Garden-Type Pump Sprayer, Low Speed Floor Buffer w/brush attachment and applicable cleaning pads, wet vac with squeegee attachment, Dip tank or soak vessel.

Manual Tool Options:
Microfiber mops, cleaning pads, scouring pads, brush, wiping cloths, empty buckets, water, etc.

Miscellaneous Items:

1. Surface Preparation Materials:
a) Paint Stripper & HD Solvent: EcoFast 100 HD Paint Stripper is used for to remove glues, adhesives, black tire marks, scuff marks, and more.

b) Concrete Etcher: Eco-Etch Pro Concrete Etcher and Cleaner. Used to etch and remove the top micro-layers of the concrete enabling a deeper clean to make concrete look new again.

STEP 03

APPLICATION

Always test surfaces for color fastness and material compatibility, especially on delicate upholstery and other dyed materials.

Dilute with water using the guidelines below. Apply liberally by bottle sprayer, pump sprayer, or powerwasher.

1. Let dwell on surface for 1-2 minutes. Heavy soil, oil, or grease may require scrubbing. This helps change the surface tension to release the soils more thoroughly.
2. Wipe, scrub, or rinse off. When spot treating carpet or upholstery, blot dry with a damp cloth or towel.
3. Repeat treatment as necessary. For best results use above 45° F. Heating up to 140° F accelerates and enhances cleaning efficacy.

DILUTION GUIDELINES

Heavy Cleaning: Use full strength or dilute up to 4:1 with water. (oil, grease, carbon deposits, etc.)

Medium Cleaning: Dilute 5:1 up to 10:1 with water. (wood decks, fences, stucco, brick pavers, restrooms, counters, sinks, showers, tubs, tile, decks, marine fiberglass & gelcoat, canvas, etc.)

Light Cleaning: Dilute 11:1 up to 30:1 with water. (vinyl, linoleum, laminates, marble, granite, decorative concrete, colorfast carpet, upholstery, etc.)

STEP 04

CLEANING TIPS

Eco-Fast™ 500 Heavy Duty Cleaner/Degreaser is a powerful concentrated and 100% non toxic plant-based cleaner formulated for difficult cleaning tasks. It can be used in concentrate form for the most difficult jobs or diluted for application specific cleaning. Eco-Fast™ 500 Cleaner has incredible oil and soil lifting power, yet contains no butyls, abrasives, or phosphates.

USE TO CLEAN:

- Concrete Floors
- Wood Floors
- Graying Wood Decks & Fences
- Exterior House & Buildings
- Driveways & Walkways
- Pool Decks & Furniture
- Masonry, Brick, & Block
- Stone Tiles
- Laminate Floors
- Canvas Materials
- Vinyl Siding & Fiber Cement Siding
- Vehicles, Equipment, & Tools
- Marine Applications
- Automotive Interior & Exterior
- Engine Parts

and so much more...

